



## NEROLAC BEAUTY SILVER SILKY FINISH INTERIOR EMULSION



**KANSAI  
NEROLAC**  
PAINTS LIMITED

Nerolac House, Ganpatrao Kadam Marg, Lower Parel, Mumbai 400013.

### PRODUCT DESCRIPTION

Nerolac Beauty Silver is a high quality water based, matt finish paint for beautifying and protecting interior walls. It is formulated by using an ideal combination of pigments and extenders, dispersed in a copolymer emulsion for smooth and pleasant matt finish

### PERFORMANCE FEATURES & BENEFITS

- Smooth and pleasing matt finish.
- Ease of application.
- Good Washability.
- Economical product with optimum performance.
- Good fungal resistance.

### RECOMMENDED USAGE


Nerolac Beauty Silky Smooth Finish Interior Emulsion is recommended for interior wall surfaces such as ceilings, plaster, bricks, asbestos, etc.

### SURFACE PREPARATION

Ensure the surface is clean, dry free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down using suitable abrasive paper and thereafter wipe off. Treat fungus affected area using Nerolac Fungicidal Solution. Allow it to react for 6 - 8 hrs. Apply a coat of suitable Primer\* followed by Nerolac wall Putty to level the dents and make the surface uniform. Apply again a coat of suitable Primer\*. Then apply two to three coats of Nerolac Beauty Silky Smooth Finish Interior Emulsion.

### RECOMMENDED SYSTEM FOR APPLICATION

For New Masonry Surfaces



For Repainting on Smooth Lime / Distemper / Emulsion / Enamel Masonry Surfaces



Sand the Surface with Emery Paper and Wipe clean before application of subsequent coats.  
\*Nerolac Cement Primer (Water Thinnable /Solvent Thinnable) or Goody Universal Primer (Solvent Thinnable) or Goody Water Thinnable Cement Primer  
# Minimum 8 Hrs for Solvent Thinnable Primer & Minimum 4 - 6 Hrs for Water Thinnable Primer.

### TECHNICAL DATA

Coverage**	210 - 240 sq. ft/ltr/coat. When applied smooth and non-absorbent surface.
Drying Time	Surface Dry: 30 minutes.
@27° ± 2°C & RH 60 ± 5%	Recoating: 4 - 6 hrs.
Gloss Levels/ Sheen levels	Matt.
Thinning	60 - 70% by volume using water
Flash Point	NA.
Stability of Thinned Paint	Use within 24 hrs.

\*\* Actual coverage may vary depending on Method, Condition of Application, Surface Porosity & Shade

### PRECAUTIONS

- 1) Refer MSDS for "Nerolac Beauty Silky Smooth Finish" for safety measures & precautions.
- 2) Store in well ambient conditions, ventilated locations & away from the source of ignition and fire.
- 3) Keep away from children.
- 4) In case of eye/skin contact, wash with plenty of water.
- 5) Inhalation / Injection dangerous. In either case, move to fresh air & consult medical practitioners.
- 6) Do not apply when ambient temperature might drop to level below 10°C within 4 hrs of application.
- 7) New plaster should be allowed to cure for minimum 12 weeks.
- 8) Avoid extra thinning for better results.
- 9) Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
- 10) The container must be tightly closed when not in use. Stir well and strain before use.
- 11) Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face mask.

### POST APPLICATION INSTRUCTIONS

Surfaces painted with NBSSFIE are washable by sponging with mild soap and water after a minimum of 2 weeks drying to remove ordinary stains and everyday dirt.

### SAFETY FEATURES

Non-Flammable.

### PACK SIZES

1 ltr, 4 ltrs., 10 ltrs. & 20 ltrs.

### SHADE RANGE

As per Beauty Range Shade Card & Colour Scapes Fandek.