



## NEROLAC LOTUS TOUCH RICH SMOOTH FINISH INTERIOR EMULSION



**KANSAI  
NEROLAC**  
PAINTS LIMITED

Nerolac House, Ganpatrao Kadam Marg, Lower Parel, Mumbai 400013.

### PRODUCT DESCRIPTION

Nerolac Lotus Touch Rich Smooth Finish Interior Emulsion Paint meant for interior wall finishing applications to render the wall with a rich look and elegant sheen. It is based on emulsion polymer made with novel chemistry to impart good durable smooth finish with good bonding to the substrate

### PERFORMANCE FEATURES & BENEFITS

- Selected brand of micro-fine pigments to impart Whiteness and Smoothness
- Blister & Moisture free\*
- Extra coverage
- low VOC
- Very low odour
- Choice of Vibrant shade range spread evenly across the color space.

### RECOMMENDED USAGE

It is recommended for interior application to a wide variety of new or previously painted surfaces such as plaster, brickwork, cement rendering, concrete, hardboard, building boards, etc. It can be applied on ceilings and wall surfaces where a matt finish, free from irritating glares due to light reflection, is desired.

### SURFACE PREPARATION

Ensure the surface is clean, dry free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down using suitable abrasive paper and thereafter wipe off. Treat fungus affected area using Nerolac Fungicidal Solution. Allow to react for 6 – 8 hrs. Apply a coat of suitable Primer\* followed by Nerolac Wall Putty to level the dents and make the surface uniform. Apply again a coat of suitable Primer\*. Then apply two to three coats of Nerolac Lotus Touch Rich Smooth Finish Interior Emulsion.

### RECOMMENDED SYSTEM

For New Masonry Surfaces



For Repainting on Smooth Lime / Distemper / Emulsion / Enamel Masonary Surfaces



**Sand the Surface with Emery Paper and Wipe clean before application of subsequent coat\***

\* Nerolac Cement Primer (Water Thinnable/Solvent Thinnable) or Goody Universal Primer (Solvent Thinnable) or Goody Water Thinnable Cement Primer  
# Minimum 8 Hrs for Solvent Thinnable Primer & Minimum 4-6 Hrs for Water Thinnable Primer



### TECHNICAL DATA

Coverage**	On Smooth and non-absorbent surface. 270 – 300 sq. ft/ltr/coat.
Drying Time @27° ± 2°C & RH 60 ± 5%	Surface Dry : 30 minutes Recoating : After 4 - 6 hours
Gloss Levels/ Sheen levels	Sheen
Thinning	50-60% by volume using water
Flash Point	NA.
Stability of Thinned Paint	Use within 24 hrs.
Shelf- Life	1 year from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

\*\*Actual coverage may vary depending on Method, Condition of Application, Surface Porosity & Shade

### PRECAUTIONS

- 1) Refer MSDS for "Nerolac Lotus Touch Rich Smooth Finish Interior Emulsion" for safety measures & Precautions.
- 2) Store in well ambient conditions, Ventilated locations & away from the source of ignition and fire.
- 3) Keep away from children.
- 4) In case of eye/skin contact wash with plenty of water.
- 5) Inhalation / Injection will cause danger. In case move to fresh air & consult medical practitioners in both the cases.
- 6) Do not apply when ambient temperature might drop to level below 10°C within 4 hrs of application.
- 7) New plaster should be allowed to cure for minimum 12 weeks.
- 8) Avoid extra thinning for better results.
- 9) Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir well tinted paint after tinting & before application.
- 10) The container must be tightly closed when not in use. Stir well and strain before use.
- 11) Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face mask.

### POST APPLICATION INSTRUCTIONS

For removing stains sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 1 week before cleaning.

### SAFETY FEATURES

Non-Flammable.

### PACK SIZES

1 ltr, 4 ltrs, 10 ltrs & 20 ltrs.

### SHADE RANGE

As per Coloursapes Fandec & Shade Card.