

# STPInnerWrap

Glass Fibre Mat For Pipe Wrapping



STP Limited

## Description

**STPInnerWrap** is reinforced glass fibre mat of 45 GSM meeting specification AWWA C-203.

## Characteristics

Thickness (min) mm	0.33	Glass fibre mat base Weight (min): g / m <sup>2</sup>	45
Breaking strength, avg. min		Porosity (mm of water)	0.6 – 1.9
• Longitudinal	2280 N/m	Pliability	No Cracking
• Transverse	700 N/m		

## Application

- Wrapping over pipe before application of hot ShaliEnamel P/R.
- Holding hot ShaliEnamel P/R on pipe surface.

## Advantages

- Rot-proof.
- Excellent resistance to soil erosion
- Provides reinforcement to the coating system
- Facilitates coating with high electrical resistance with regard to cathodic protection.

## Application Methodology

- **STPInnerWrap** is dry glass fibre tissue used for anti corrosive wrapping coating as inner reinforcement layer for ShaliEnamel P/R.
- A minimum overlap of 25 mm with a tension during application is required to avoid wrinkles, buckles and allowing even bleed outs.
- Standard practice is to use one / two layers of **STPInnerWrap**.

## Health & Safety

- Use goggles, hand gloves and mask while application.
- Clean hands with warm soap water after application.

## Packing

Available in rolls of 300 M in length and normally 6 / 9 / 12 / 18 / 36 Inch in width.

## Storage

Keep in cool dry place, under the shed, away from heat.

---



**Advisory Cell**  
STP Limited  
**+91 81302 81114**  
Waterproofers to the Nation

**STP's Businesses**

Waterproofing & Insulation  
Road Surfacing  
Pipeline Coating  
Repairs & Rehabilitation  
GARA (Grouts & Admixtures)  
Other Powder Products  
Sealant & Additives  
Epoxy Flooring  
Protective / Anti-Corrosive Coating  
Other Products



Call us : +91 98250 27368  
Nilkamal Paints & Hardware

Visit us at : [www.stpltd.com](http://www.stpltd.com) or Email at : [info@stpltd.com](mailto:info@stpltd.com)