# ShaliBond® BS / CS



**Cold Applied Bituminous Adhesive For Fixing Roofing Felts** 

# **Description**

**ShaliBond® BS / CS** is a cold applied bituminous adhesive for fixing waterproofing membrane. It is manufactured from special grades of bitumen, suitably blended with other additives. It has semiliquid consistency and is ready to use.

#### **Characteristics**

Colour	Black	Dry Film Thickness	150 microns
Viscosity in sec (10 mm cups)	15 - 20	Theoretical Coverage, kg/m <sup>2</sup> *	
Consistency	Brushable	On metal surface	0.50
Drying Time, hr	24	On concrete surface	0.70
Specific Gravity	0.95	Flash Point	40 °C

<sup>\*</sup> Depending upon surface condition.

# **Application**

Recommended for sticking roofing felts on metal, timber, tiles, asbestos, concrete and masonry surfaces, including roofs of trains, buses, tramcars, railway carriages, etc.

### **Advantages**

ShaliBond BS/CS is cold applied adhesive and does not require any torching. Therefore, it is useful for applications where use of hot bitumen / torching is difficult or prohibited.

# **Application Methodology**

- Surfaces should be cleaned of all foreign materials and should be completely dry.
- Apply ShaliBond BS / CS over the cleaned surfaces with a spatula or brush.
- Allow approximately 10 minutes time before laying the felt and sticking the same by application of uniform mild pressure.
- For more effective waterproofing, seal overlaps and termination by affixing 6 inch flashings of the membrane on overlapping area after application of ShaliPrime APP.

# **Health & Safety**

- Lid of the container should be firmly fixed, when not in use.
- ShaliBond® BS / CS is inflammable and hence keep away from flame.
- Use goggles and hand gloves during application.
  - Clean hands with warm soap water after application

#### **Packing**

Available in 1 kg, 4 kg, 18 Kg and 180 kg drums.

#### Storage

Keep in cool and dry place, in air tight container, under shed, away from heat.



#### STP's Businesses

Waterproofing & Insulation **Road Surfacing Pipeline Coating Repairs & Rehabilitation GARA (Grouts & Admixtures) Other Powder Products** 





Visit us at : www.stpltd.com or Email at : info@stpltd.com