ShaliPrime Penetration



Single Component Aromatic Polyurethane Primer

Description

ShaliPrime Penetration is single component polyurethane based low viscous highly penetrative primer.

Characteristics

4 - 5	Surface Dry, @ 30 °C	35 – 45 minute
24 Max	Theoretical Coverage, m ² /	8 - 10
15 - 20	L/coat *	
condition.		9 .0
aces.	13	700
	A	
	pared concrete surfaces.	10.
	24 Max 15 - 20 e condition. faces.	24 Max Theoretical Coverage, m²/ L/coat * condition. faces.

Depending upon surface condition.

Application

Advantages

- Better adhesion and flexibility.
- Chemical resistance.
- Improved performance over manually prepared concrete surfaces.

Application Methodology

- In case of concrete surface, ensure that concrete is firm, sound and even.
- Clean thoroughly and dry. Remove all dirt, scales, oil, grease and foreign particles.
- In case of steel surface, clean surface thoroughly by sandblasting or power tools. Remove moisture prior to sand blasting.
- Apply ShaliPrime Penetration on cleaned and dried surface by brush or airless spray.

Health & Safety

- The product should not come in contact with the skin and eyes, or be swallowed.
- Ensure adequate ventilation and avoid inhalation of vapours as some people are sensitive to resins, hardeners and solvents.
- Wear suitable protective clothing, gloves and eye protection.
- In case of contact with skin, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical
- If swallowed seek medical attention immediately do not induce vomiting.

Packing

Available in 20 L container.

Storage

Store in a cool dry place, under shed, away from heat.

Shelf Life

12 months in original unopened sealed condition.



STP's Businesses

Waterproofing & Insulation **Road Surfacing Pipeline Coating Repairs & Rehabilitation GARA (Grouts & Admixtures)**



