

ShaliSeal CPM

Cementitious Polymerised Mortar for Sealing / Crack Filling / Repair



STP Limited

Description

ShaliSeal CPM is designed as industrial grade sealing and repairing compound for upgrading or renovating new and existing floors and screeds. The polymer modified powdery material is ready to use for industrial, commercial or household purpose.

Characteristics

Appearance	Gray, cement colour powder	Adhesive Strength Concrete-V tiles	2 MPa Cohesive Failure
Mixing ratio with water	100 : 33	Water Pressure Test EN 14891	Water Loss -0 cc in 7 days, Penetration -0.5 cc in 7 days
Compressive Strength	14 MPa		
Flexibility ISO 527, %	7		

Application

- Old mortar / screed showing water seepage through cracks
- All kind of structural repair which requires hand application / brush
- Roof under the water tank on the roof top
- Basement vertical wall plastering
- Underlayment of medium duty flooring with small gravel dust.

Advantages

- Excellent crack bridging nature
- Very low shrinkage
- Very good adhesion with old and new mortar / concrete
- Resistant to carbon di oxide attack
- Good water vapour permeability

Application Methodology

- Apply on clean, dry and sound concrete substrates that are free of all coatings, sealers, curing compounds, oils greases or any other contaminants.
- Ensure substrate is firm and fully cured. Concrete and sand / cement screeds must be sound, dry and fully cured (not subject to shrinkage) and any laitance or treatments must be removed by mechanical means such as grit blasting.
- Mix powder in water in the ratio of 3 : 1.
- Slowly stir the mixture for a homogenous content for about 20 – 30 minutes. Stirring should be done in a way to avoid induction of air bubbles.
- Apply the mass by brush / trowel depending upon its use for filling or repairing purpose. Any bags forming lumps must be removed from the stack.
- Do not apply when the temperature is less than 5 °C or when the weather is foggy.

Health & Safety

- Use goggles and hand gloves during application.
- Clean hands with warm soap water after application.

Packing

Available in 20 kg poly bag.

Storage

Keep in well ventilated dry place in packed condition under shed, away from heat / direct sun light / high humidity.



STP's Businesses
Waterproofing & Insulation
Road Surfacing
Pipeline Coating
Repairs & Rehabilitation
GARA (Grouts & Admixtures)
Other Powder Products
Sealant & Additives
Epoxy Flooring
Protective / Anti-Corrosive Coating
Other Products

