

# SHINGAR MAX SUPERIOR EXTERIOR EMULSION



Shingar Max is a water based 100 % Acrylic Exterior wall finish which is suitable for dry or moderately humid climatic conditions .

## TECHNICAL DATA

<b>Areas of Application</b>	:	Cement Plaster, Asbestos Sheet, concrete etc.
<b>Viscosity of Supply</b>	:	100-112 Krebs Units on Stormier Viscometer at 30°C
<b>Consistency</b>	:	Smooth and free-flowing
<b>Thinner</b>	:	Municipal / Potable Water
<b>Thinner Ratio</b>	:	75% by volume with water for each Coat
<b>Method of Application</b>	:	Brush / Roller
<b>Drying Time</b>	:	Touch Dry in 30 minutes. Recoating period about 4-6 Hrs.
<b>Coverage on normal to rough cement plaster</b>	:	55-65 sq. ft. / ltr / 2 coats
<b>Finish</b>	:	Smooth and Matt
<b>Shades available</b>	:	As per shade card
<b>Packs available</b>	:	20 ltr, 10 ltr, 4 ltr & 1 ltr



## DIRECTIONS FOR USE

- The surface to be painted should be cleaned of all loose paint, dust grease and fungus or algae growth.
- Only using cement plaster should fill imperfections of surface.
- Shingar Max should be applied by thinning 1 ltr of paint with 400 ml. of water with a gap of 4-6 hours between coats.
- Use of Shield White Cement Based Wall Putty and Acrylic Exterior Wall Primer is recommended to set a smooth and better finish.
- Shingar Max can be applied by brush or roller.

(The information herein is given in good faith. Covering capacity is indicated on the basis of results obtained on a prepared smooth surface).



Call us: +91 98250 27368  
Nilkamal Paints & Hardware

## Special Features

3 Year Warranty | Anti Fungal | Anti Peeling | Anti Algae | Non Fading | Available in White & Base White



SHINGAR MAX SUPERIOR EXTERIOR EMULSION